

SUPERHAUL 18

Specifications

Model AUT8118-70 / AUT8118-10

| | |
|--|---|
| Marketing Name | SUPERhual 18 |
| GVWR (lbs) | 10,000# |
| GAWR (lbs/axle) | 5200# |
| Curb Weight (Base) | 1870# / 1955# |
| Payload | 5130# / 8045# |
| Frame Construction | 6" Tube |
| Frame Wall Thickness | 3/16"-1/4" |
| Tounge Length (Deck to Ball) | 56" |
| Tongue | 6" Tube A-Frame |
| Coupler | 2-5/16" |
| Jack | 5000# Top wind |
| Fenders | 1/8" smooth aluminum, removable |
| Suspension | Torsion Axle (Galv) |
| Axle spacing | Standard (33" CTC) |
| Brakes | 10" Electric self Adjust / 12" Electric self Adjust |
| Tires | 225/75R15 Load Range D |
| Wheels | 15", 6 on 5.5 / 15", 6 on 5.5 |
| Decking | Aluminum |
| Lighting | LED |
| Electical | 7-Way RV-Style Molded Plug |
| Overall length | 282" |
| Bed Length | 216 |
| Bed Width | 81" |
| Beaver Tail | N/A |
| Width Between Wheel Wells | 83" |
| Distance from trailer front to front of wheel wells | 95" |
| Distance from back of trailer to back of wheel wells | 53" |
| Deck Height | 24" |
| Coupler Height | 20" |
| Ramp | 6.5' straight ramps |
| Extended Ramp Length | 80" |
| Optional Front Rock Guard Height | 50" |

Standard SP

- Tongue Tool box
- Front Rail
- Stake pockets (fits 2X4)
- Rub rail
- Straight Ramps
- Safety chains
- Towing organizer for 7 way plug and safety chains
- Backup Lights
- Stainless Steel Hardware

Options

- Spare Tire
- Winch (winch, mount, battery tray, electrical)
- Reverse winch kit (D-Ring and Pulley)
- Rock Guard (48" and 36")
- Side Ramps (1 set)
- Loading Guides
- Full width Bifold w/ Spring Assist