

SUPERHAUL 26

Specifications

Model AET8126-10S

Marketing Name	SUPERhaul 26
GVWR (lbs)	10,000#
GAWR (lbs/axle)	5200#
Curb Weight (Base)	2285#
Payload	7715#
Frame Construction	6" Tube
Frame Wall Thickness	3/16"-1/4"
Tounge Length (Deck to Ball)	56"
Tongue	6" Tube A-Frame
Coupler	2-5/16"
Jack	5000# Top wind
Fenders	1/8" smooth aluminum, removable
Suspension	Torsion Axle (Galv)
Axle spacing	S Models (42" spread)
Brakes	10" Electric self Adjust / 12" Electric self Adjust
Tires	225/75R15 Load Range D
Wheels	15", 6 on 5.5 / 15", 6 on 5.5
Decking	Aluminum
Lighting	LED
Electical	7-Way RV-Style Molded Plug
Overall length	378"
Bed Length	312
Bed Width	81"
Beaver Tail	N/A
Width Between Wheel Wells	83"
Distance from trailer front to front of wheel wells	134.5"
Distance from back of trailer to back of wheel wells	102"
Deck Height	24"
Coupler Height	20"
Ramp	6.5' straight ramps
Extended Ramp Length	80"
Optional Front Rock Guard Height	50"

Standard

- Tongue Tool box
- Front Rail
- Stake pockets (fits 2X4)
- Rub rail
- Straight Ramps
- Safety chains
- Towing organizer for 7 way plug and safety chains
- Backup Lights
- Stainless Steel Hardware

Options

- Spare Tire
- Winch (winch, mount, battery tray, electrical)
- Reverse winch kit (D-Ring and Pulley)
- Rock Guard (48" and 36")
- Side Ramps (1 set)
- Loading Guides
- Full width Bifold ramp w/ Spring Assist